·	Inco Type 210 INCO® Type	Incofoam INCOFOAM®
	210 nickel powder	porous nickel substrate
Br ₂ holding capacity	27g/50ml	

At page 38, replace the Abstract of the Disclosure with the following new Abstract of the Disclosure, as also set out in identical form on a separate page attached to this Amendment:

ABSTRACT OF THE DISCLOSURE

The invention relates to a A fluid storage and delivery system utilizing a porous metal matrix that comprises at least one Group VIIIB metal therein. In one aspect of the invention, such embodiment, the porous metal matrix forms a solid-phase metal adsorbent medium, characterized by with an average pore diameter of from about 0.5nm to about 2nm and a porosity of from about 10% to about 30%, —Such solid-phase metal adsorbent medium which is particularly useful for sorptively storing and desoprotively desorptively dispensing a low vapor pressure fluid, e.g., ClF₃, HF, GeF₄, Br₂, etc. In another aspect, of the invention, such the porous metal matrix forms a solid-phase metal sorbent, characterized by with an average pore diameter of from about 0.25µm to about 500µm and a porosity of from about 15% to about 95%, which can effectively immobilize low vapor pressure liquefied gas and prevent the same from entering the fluid regulator as described in U.S. Patent No. 6,089,027.

ABSTRACT OF THE DISCLOSURE

The invention relates to a A fluid storage and delivery system utilizing a porous metal matrix that comprises at least one Group VIIIB metal therein. In one aspect of the invention, such embodiment, the porous metal matrix forms a solid-phase metal adsorbent medium, characterized by with an average pore diameter of from about 0.5nm to about 2nm and a porosity of from about 10% to about 30%, Such solid-phase metal adsorbent medium which is particularly useful for sorptively storing and desopretively desorptively dispensing a low vapor pressure fluid, e.g., CIF₃, HF, GeF₄, Br₂, etc. In another aspect, of the invention, such the porous metal matrix forms a solid-phase metal sorbent; characterized by with an average pore diameter of from about 0.25µm to about 500µm and a porosity of from about 15% to about 95%, which can effectively immobilize low vapor pressure liquefied gas and provent the same from entering the fluid regulator as described in U.S. Patent No. 6,089,027.